Distributed by:

JAMECO® ELECTRONICS

www.Jameco.com ✦ 1-800-831-4242

The content and copyrights of the attached material are the property of its owner.

Jameco Part Number 223141 (745254-6)

DRAWING MADE IN THIRD ANGLE PROJECTION

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION ,19 .
© COPYRIGHT 19 BY AMP INCORPORATED, HARRISBURG, PA. ALL INTERNATIONAL RIGHTS RESERVED. AMP PRODUCTS MAY BE COVERED BY U.S. AND FOREIGN PATENTS AND/OR PATENTS PENDING.

LOC	DIST
BD	48

P	F	ZONE	LTR	DESCRIPTION	DATE	APPD
				REVISIONS		
			A	REVISED & REDRAWN ECN-1606	7-28-86	–
			A1	ADDED 1--7 PER NPR 4837	06/15/93	SB
			B	REV PER EC 0420-0036-96	14 OCT 96	PF
			C	OBS -17 PER EC 0420-141-96	18 SEPT 97	SB
			D	REV PER EC 0420-163-97	09 FEB 98	PR
			E	REV PER EC 0G40-27-98	22 JUN 98	JK
			F	REV PER EC 0G40-102-99	01 MAR 99	JK
			G	REV PER EC 0G40-441-98	18 MAR 99	RT





SECTION X–X
INSULATION BARREL
SCALE 20:1



SECTION Y–Y
WIRE BARREL
SCALE 20:1

1. FOR MINI-APPLICATOR.
2. FOR HAND TOOL USE ONLY.
3. WIRE RANGE OF 22-26, INSULATION RANGE OF .040-.050.
4. GOLD PLATING MAY NOT APPEAR ON CARRIER STRIP.
5. GOLD PLATING PER MIL-G-45204, NICKEL PLATING PER QQ-N-290, TIN PLATING PER MIL-T-10727.
6. GOLD PLATED IN LOCALIZED GOLD PLATED AREA, .000030 GOLD IN MATED AREA, GOLD FLASH ON REMAINDER, OVER .000050 NICKEL.
7. 0.025µm [.000001] MIN GOLD OVER .000030 NICKEL.
8. GOLD PLATED IN LOCALIZED GOLD PLATED AREA, 0.025µm [.000001] MIN GOLD IN MATED AREA, TIN PLATED WIRE BARRELS, OVER .000030 NICKEL.
9. GOLD PLATED IN LOCALIZED GOLD PLATED AREA, .000030 GOLD IN MATED AREA, TIN PLATED WIRE BARRELS, OVER .000050 NICKEL.

	PACKAGING TYPE	FINISH	USE	TYPE	PART NUMBER
OBSOLETE	SMALL PACK	7	2	LOOSE PIECE	1-745254-7
	STANDARD	9	2	LOOSE PIECE	1-745254-6
	STANDARD	9	1	STRIP	1-745254-4
	STANDARD	8	2	LOOSE PIECE	1-745254-3
	STANDARD	8	1	STRIP	1-745254-1
	STANDARD	7	2	LOOSE PIECE	745254-7
	STANDARD	6	2	LOOSE PIECE	745254-6
	STANDARD	7	1	STRIP	745254-3
	STANDARD	6	1	STRIP	745254-2

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES
TOLERANCES ON :
2 PL DEC ± -
3 PL DEC ± .005
ANGLES ± -

MATERIAL
BRASS PER MIL-C-50

FINISH 5
SEE TABLE

DR 9-9-86 S.WELDON
CHK 9-9-86 C.RICHARD
APPD 9-10-86 L.BREKOSKY
APPD 9-10-86 V.KUMAR
PRODUCT SPEC –
APPLICATION SPEC 114-10000
WEIGHT –

AMP | AMP INCORPORATED Harrisburg, Pa. 17105

NAME
PIN CONTACT, SIZE 20 DF, 22-26 AWG, W/.040-.050 DIA INSULATION SUPPORT

SIZE	FSCM NO	DRAWING NO
C	00779	745254

SCALE		SHEET
10:1		1 OF 1

745254

AMP 1471-7 REV 10-84

CUSTOMER DRAWING